NSN 3020-00-541-5012

Spur Gear - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/3020-00-541-5012

Webbed, offset, solid				
Pitch Diameter:				
1.0416 inches				
Teeth Quantity:				
50				
Bore Style:				
W/ keyway both ends				
Hardness Rating:				
23.0 rockwell c and 30.0 rockwell c				
Outside Diameter:				
1.0813 inches				
Tooth Form:				
Standard				
Pressure Angle:				
14.5000 degrees				
Distance Between Body Face And Protruding Hub End:				
0.0500 inches second end				
Face Width:				
0.125 inches				
Bore Diameter:				
0.240 inches both ends				
Keyway Width:				
0.062 inches both ends				
Distance From Bore Center To Keyway Bottom:				
0.166 inches both ends				
Hub Style Designator:				
Plain second end				
Hub Diameter:				
0.5310 inches second end				
Precision Classification:				
Quality number 10				
First Groove Width:				
0.0320 inches first end				
First Groove Diameter:				
0.4120 inches first end				
Distance From End To First Groove:				
0.0425 inches first end				
Material:				
Steel comp 416				
Material Specification:				
Qq-s-763 federal specification single material response				

NSN 3020-00-541-5012

Spur Gear - Page 2 of 2



_	•	_		
	irtac	_O Irα	aatm	ent:
J	ui iau	C 110	sauı	ICIIL.

Passivate

Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300