## NSN 3020-00-542-0474

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-542-0474

**Body Style:** Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 2.0830 inches **Teeth Quantity:** 100 **Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end Mounting Hole Thread Size: 0.086 inches transversely through hub, first end Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end **Outside Diameter:** 2.124 inches Nominallength: 0.281 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.228 inches first end Face Width: 0.052 inches **Bore Diameter:** 0.188 inches both ends Hub Style Designator: 1 step first end End Length: 0.146 inches first end End Diameter: 0.313 inches first end First Step Length: 0.025 inches first end **First Step Diameter:** 0.374 inches first end

# NSN 3020-00-542-0474

Spur Gear - Page 2 of 2



Second Step Length:

0.057 inches first end

### Second Step Diameter:

0.499 inches first end

Material:

Aluminum alloy 2024

## Material Specification:

Qq-a-268, t4 federal specification single material response

#### Surface Treatment:

Anodize

#### Style Designator:

Protruding hub

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A27300