NSN 3020-00-542-1744



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-542-1744 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 3.2500 inches **Teeth Quantity:** 156 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc axially through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 32 axially through hub, first end **Mounting Hole Thread Size:** 0.138 inches axially through hub, first end **Mounting Hole Type And Quantity:** 4 threaded axially through hub, first end **Outside Diameter:** 3.2917 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.2300 inches first end **Face Width:** 0.064 inches **Bore Diameter:** 0.2500 inches both ends

0.2000 11101100 20111 01100
Hub Style Designator:
1 step first end
End Length:
0.9950 inches first end
End Diameter:
0.7480 inches first end
First Step Length:
0.1820 inches first end
First Step Diameter:
0.0660 inches first end
Material:
Copper alloy

NSN 3020-00-542-1744

Spur Gear - Page 2 of 2



_	•		_			
<u>ن</u>	irta	\sim	Irο	atm	nan	
υı	ai ia	ᅜ	116	аш		ı.,

Nickel

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300