NSN 3020-00-542-4954

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-542-4954 Pitch Diameter: 1.8750 inches **Teeth Quantity:** 90 **Bore Style:** Plain first end **Backlash Designation:** Grade c **Outside Diameter:** 1.914 inches Nominallength: 0.406 inches **Tooth Form:** Standard **Pressure Angle:** 14.5000 degrees Distance Between Body Face And Protruding Hub End: 0.219 inches first end **Face Width:** 0.187 inches **Bore Diameter:** 0.563 inches first end **Hub Style Designator:** Plain first end **Hub Diameter:** 0.933 inches first end **Precision Classification:** Quality number 8 or quality number 12 **Special Features:** Counterbore second end, 0.703 in. Dia; 0.188 in. Deep Material: Aluminum alloy 2024 **Material Specification:** Qq-a-225/4, t4 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response **Style Designator:** Protruding hub Shelf Life:

N/a

NSN 3020-00-542-4954

Spur Antibacklash Gear - Page 2 of 2



ш	Inıt	· / 1+	Measure	

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.