NSN 3020-00-546-9763

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-546-9763 Pitch Diameter: Between 1.9772 inches and 1.9792 inches **Teeth Quantity:** 95 **Bore Style:** W/ keyway both ends **Outside Diameter:** 2.019 inches Nominallength: 0.328 inches **Tooth Form:** Standard **Pressure Angle:** 14.5000 degrees **Distance Between Body Face And Protruding Hub End:** 0.132 inches first end **Face Width:** 0.183 inches **Bore Diameter:** 0.240 inches both ends **Keyway Width:** 0.062 inches both ends **Distance From Bore Center To Keyway Bottom:** 0.168 inches both ends **Hub Style Designator:** 1 step first end **End Length:** 0.069 inches first end **Precision Classification:** Quality number 8 **End Diameter:** 0.625 inches first end First Step Length: 0.062 inches first end First Step Diameter: 1.000 inches first end Material: Stainless steel hub **Material Specification:**

Qq-a-250/4, t3 federal specification single material response body

Style Designator: Protruding hub

NSN 3020-00-546-9763

Spur Antibacklash Gear - Page 2 of 2



-			
٠.	hΔ	Iŧ.	ife:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300