NSN 3020-00-550-7143

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-550-7143

Body Style:
Webbed, solid
Attachment Method:
Mounting hole
Pitch Diameter:
14.0000 inches
Teeth Quantity:
56
Bore Style:
W/ 3 keyways both ends
Backlash Designation:
Grade e
Mounting Hole Thread Series Designator:
Unf axially through body, second end
Mounting Hole Thready Qty Per Inch (tpi):
32 axially through body, first end
Hardness Rating:
30.0 rockwell c and 35.0 rockwell c
Mounting Hole Thread Size:
0.190 inches axially through body, first end
Mounting Hole Type And Quantity:
2 threaded axially through body, second end
Outside Diameter:
14.397 inches
Nominallength:
2.995 inches
Tooth Form:
Stub
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.505 inches first end
Distance Between Body Face And Recessed Hub End:
0.500 inches second end
Face Width:
2.090 inches
Bore Diameter:
3.812 inches both ends
Keyway Width:
0.748 inches both ends
Distance From Bore Center To Keyway Bottom:

2.226 inches both ends

NSN 3020-00-550-7143

Spur Gear - Page 2 of 2



Hub Style Designator:
Plain both ends
Hub Diameter:
5.375 inches second end
Bolt Hole Circle Diameter:
7.000 inches axially through body, second end
Material:
Steel
Material Specification:
Mil-s-11415 military specification single material response
Surface Treatment:
Phosphate
Style Designator:
One protruding hub, one recessed hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):
Mil-s-11415 spec.