## NSN 3020-00-554-7785

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-554-7785

Attachment Method:
Mounting hole
Pitch Diameter:
2.8000 inches
Teeth Quantity:
112
Bore Style:
W/counterbore both ends
Mounting Hole Thread Series Designator:
Unc axially through body, first end
Mounting Hole Thready Qty Per Inch (tpi):
32 axially through body, first end
Hardness Rating:
16.0 rockwell c and 25.0 rockwell c teeth
Mounting Hole Thread Size:
0.164 inches axially through body, first end
Mounting Hole Type And Quantity:
3 threaded axially through body, first end
Outside Diameter:
2.849 inches
Nominallength:
0.781 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.343 inches first end
Face Width:
0.187 inches
Bore Diameter:
1.250 inches both ends
Counterbore Depth:
0.281 inches both ends
Counterbore Diameter:
1.375 inches both ends
Hub Style Designator:
Plain second end
Hub Diameter:
1.625 inches second end
End Length:
0.156 inches first end

## **NSN 3020-00-554-7785** Spur Gear - Page 2 of 2



End Diameter:
1.531 inches first end
First Step Length:
0.061 inches first end
First Step Diameter:
2.248 inches first end
Second Step Length:
0.125 inches first end
Second Step Diameter:
2.625 inches first end
Bolt Hole Circle Diameter:
1.968 inches axially through body, first end
Material:
Steel comp 8637h
Material Specification:
Fed standard 66, aisi/sae 8637h federal standard single material response
Surface Treatment:
Phosphate
Surface Treatment Specification:
Mil-c-16232 military specification single treatment response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):
Mil-c-16232 spec.