## NSN 3020-00-554-9068

Groove Pulley - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-554-9068 **Groove Depth:** 0.6248 inches **Groove Width:** 0.656 inches **Outside Diameter:** 9.000 inches **Overall Length:** 2.09375 inches **Keyway Width:** Between 0.251 inches and 0.256 inches Bore Length: 1.500 inches **Distance From Center Of Bore To Bottom Of Keyway:** Between 0.6215 inches and 0.6245 inches V Groove Angle In Deg: 38.0 **Pitch Diameter:** 8.000 inches **Taper Bore Major Diameter:** Between 0.995 inches and 0.997 inches **Taper Bore Minor Diameter:** Between 0.8075 inches and 0.8095 inches **Material And Location:** Iron, cast **Face Width:** 1.719 inches **Design Form:** Webbed **Bore Type: Tapered** Bearings: Not included **Taper Major Diameter Location:** Aa end **Groove Quantity: Counterbore Feature:** Not included **Keying Facility:** Included

**Keying Facility Type:** 

Tapered keyway

## **NSN 3020-00-554-9068** Groove Pulley - Page 2 of 2



Split Hub Feature:
Not included
Web/spoke Relationship To Face Centerline:
Offset
Lightening Hole:
Included
Integral Cooling Vane:
Not included
Groove Shape:
V
Bore Feature:
Included
Keying Facility Largest Dimension Location:
Aa end
Hub End Outside Diameter And Location:
1.625 inches aa end and 1.438 inches bb end
Distance From Outside Flange/rim To Hub End And Location:
0.375 inches aa end and 0.219 inches bb end
Quantity:
1
Style Designator:
Webbed or spoked
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-a