NSN 3020-00-562-1173



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-562-1173 **Body Style:** Plain, solid **Attachment Method:** Mounting hole **End Application:** Clark model 290m; tractor, wheeled, ind., diesel driven; med dbp, nsn 2420000889384, w/rops nsn 2420010590090 Pitch Diameter: 2.4500 inches **Teeth Quantity:** 49 **Bore Style:** W/ keyway both ends **Mounting Hole Type And Quantity:** 2 plain axially through body, first end **Outside Diameter:** 2.5475 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.3200 inches first end **Face Width:** 0.315 inches **Bore Diameter:** 0.5895 inches both ends **Keyway Width:** 0.1590 inches first end **Distance From Bore Center To Keyway Bottom:** 0.3730 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.9400 inches first end **Mounting Hole Diameter:** 0.437 inches axially through body, first end **Bolt Hole Circle Diameter:** 1.400 inches axially through body, first end

Material: Steel

Style Designator:

Protruding hub

NSN 3020-00-562-1173

Spur Gear - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300