
## NSN 3020-00-563-6572

Spur Gear - Page 1 of 2



## Body Style:

Plain, solid

#### **Attachment Method:**

Clamp

## **Pitch Diameter:**

Between 0.7490 inches and 0.7500 inches

## **Teeth Quantity:**

36

Bore Style:

Plain both ends

**Outside Diameter:** 

## 0.791 inches

Tooth Form:

#### Standard

Pressure Angle:

#### 20.0000 degrees

### Distance Between Body Face And Protruding Hub End:

0.281 inches first end

#### Face Width:

0.125 inches

## Bore Diameter:

0.125 inches both ends

## Hub Style Designator:

Split first end

## Hub Diameter:

0.188 inches first end

### **Clamping Surface Length:**

0.250 inches first end

## **Precision Classification:**

Quality number 10 or quality number 11

## Material:

Steel comp 303

### **Material Specification:**

Qq-s-764, type 303, cond a federal specification single material response

### Surface Treatment:

Passivate

## Surface Treatment Specification:

Qq-p-35, type 1 federal specification single treatment response

#### Style Designator:

Protruding hub

#### Shelf Life:

N/a



# NSN 3020-00-563-6572

Spur Gear - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

