NSN 3020-00-563-6580

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-563-6580 **Pitch Diameter:** Between 0.7480 inches and 0.7500 inches **Teeth Quantity:** 24 **Bore Style:** Plain both ends **Hardness Rating:** 75.0 rockwell b and 90.0 rockwell b **Outside Diameter:** 0.813 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.312 inches first end **Face Width:** 0.250 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.500 inches first end **Precision Classification:** Quality number 10 Material: Steel comp 303 **Material Specification:** Qq-s-763, cond c federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Style Designator:** Protruding hub **Furnished Items And Quantity:** 1 setscrew Shelf Life:

Unit Of Measure:

N/a

NSN 3020-00-563-6580

Spur Antibacklash Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-f-14072 spec.