NSN 3020-00-569-7367

Spur Gear - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/3020-00-569-7367 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 2.6250 inches **Teeth Quantity:** 21 **Bore Style:** W/counterbore first end **Mounting Hole Type And Quantity:** 2 plain axially through body, first end **Outside Diameter:** 2.875 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Face Width: 0.375 inches **Bore Diameter:** 0.923 inches first end **Counterbore Depth:** 0.250 inches counterbore, first end **Counterbore Diameter:** 1.250 inches counterbore, first end **Mounting Hole Diameter:** 0.120 inches axially through body, first end and 0.300 inches axially through body, first end **Bolt Hole Circle Diameter:** 0.560 inches axially through body, first end and 0.812 inches axially through body, first end Material: Steel comp 1018 or steel comp 1025 **Material Specification:** Astm a108-73 assn standard all material responses **Surface Treatment:** Phosphate manganese or phosphate zinc **Surface Treatment Specification:** Mil-std-171 fn 5.3.1.2 or 5.3.2.2 military standard all treatment responses **Style Designator:** Hubless Shelf Life:

NSN 3020-00-569-7367

Spur Gear - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-std-171 spec.