NSN 3020-00-571-3683

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-571-3683

Outside Diameter:
2.529 inches
Overall Length:
Between 0.807 inches and 0.812 inches
Bore Diameter:
Between 0.4726 inches and 0.4731 inches
Bore Length:
Between 0.807 inches and 0.812 inches
Drilled Hole Diameter:
0.093 inches
Pitch Diameter:
2.392 inches
Securing Hole Quantity:
1
Face Width:
Between 0.103 inches and 0.110 inches
Guide:
Not included
Design Form:
Plain
Bore Type:
Straight
Metallic Hardness Rating And Location:
26.0 rockwell c body and 33.0 rockwell c body
Counterbore Feature:
Not included
Hole Location:
On bb hub od
Keying Facility:
Not included
Securing Method:
Drilled hole
Lightening Hole:
Not included
Protruding Hub Characteristic:
Plain
Securing Location:
Bb end
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:

Single pitch

NSN 3020-00-571-3683 Sprocket Wheel - Page 2 of 2



Teeth Row Quantity:
1
Teeth Quantity Per Row:
30
Hardness Rating Test Method:
Rockwell
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.250 inches
Hub End Outside Diameter And Location:
0.750 inches both ends
Distance From Outside Flange/rim To Hub End And Location:
0.355 inches aa end and 0.347 inches bb end
Material:
Steel, mil-s-6758
Material:
Steel comp 4130
Material Specification:
Mil-s-6758 military specification single material response
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c
Mil-std (military Standard):
Mil-s-6758 spec.