

View Online at <https://aerobasegroup.com/nsn/3020-00-578-2241>

Body Style:

Webbed, offset, with lightening holes

Attachment Method:

Mounting hole

Pitch Diameter:

3.5646 inches

Teeth Quantity:

105

Bore Style:

Plain both ends

Backlash Designation:

Grade c

Hardness Rating:

58.0 rockwell h teeth and 62.0 rockwell h teeth

Mounting Hole Type And Quantity:

1 plain transversely through hub, first end

Outside Diameter:

3.6094 inches

Teeth Type:

Single helix

Tooth Form:

Stub

Tooth Direction:

Left

Pressure Angle:

20.0000 degrees

Helix Angle:

23.0000 degrees

Distance Between Body Face And Protruding Hub End:

0.625 inches first end

Face Width:

0.438 inches

Bore Diameter:

0.5001 inches both ends

Hub Style Designator:

Plain second end

Hub Diameter:

1.000 inches second end

End Length:

0.6250 inches first end

Precision Classification:

Quality number 10

End Diameter:

0.7874 inches first end

First Step Length:

0.1250 inches first end

First Step Diameter:

1.0000 inches first end

Mounting Hole Diameter:

0.062 inches transversely through hub, first end

Material:

Steel comp e9310

Material Specification:

Ams 6260 assn standard single material response

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924, class 2 military specification single treatment response

Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-c-13924 spec.