

View Online at <https://aerobasegroup.com/nsn/3020-00-580-3056>

Groove Depth:

0.647 inches

Groove Width:

0.500 inches

Outside Diameter:

7.313 inches

Overall Length:

5.844 inches

Keyway Width:

0.250 inches

Bore Length:

5.813 inches

Distance From Center Of Bore To Bottom Of Keyway:

1.281 inches

V Groove Angle In Deg:

36.000

Pitch Diameter:

6.031 inches

Taper Bore Major Diameter:

2.813 inches

Taper Bore Minor Diameter:

2.125 inches

Material And Location:

Iron

Face Width:

2.375 inches

Design Form:

Plain

Bore Type:

Tapered

Bearings:

Not included

Taper Major Diameter Location:

Bb end

Groove Quantity:

3

Counterbore Feature:

Not included

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Secured by keyway

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Not offset

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

V

Bore Feature:

Included

Protruding Hub Characteristic:

Grooved

Hub End Outside Diameter And Location:

2.938 inches aa end

Distance From Outside Flange/rim To Hub End And Location:

2.188 inches aa end

First Step Face Largest Diameter And Location:

3.750 inches aa end

Second Step Face Largest Diameter And Location:

4.250 inches aa end

First Step Length And Location:

1.188 inches aa end

Second Step Length And Location:

0.375 inches aa end

First End Groove Diameter And Location:

4.500 inches aa end

First End Groove Width And Location:

0.938 inches aa end

First End Length From Groove To End And Location:

2.719 inches aa end

Special Features:

Six 3/8 in. Mtg holes on 3-7/8 in. Bolt hole circle on face of bb end for mtg a vibration damper assembly

Quantity:

1

Style Designator:

Plain

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T353-a