NSN 3020-00-580-4313

Spur Gear - Page 1 of 2

Body Style: Plain, solid

Attachment Method:



View Online at https://aerobasegroup.com/nsn/3020-00-580-4313

Mounting hole
Pitch Diameter:
1.5000 inches
Teeth Quantity:
96
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
40 transversely through hub, first end
Mounting Hole Thread Size:
0.112 inches transversely through hub, first end
Mounting Hole Type And Quantity:
2 threaded transversely through hub, first end
Outside Diameter:
1.530 inches
Nominallength:
0.375 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.219 inches first end
Face Width:
0.156 inches
Bore Diameter:
0.250 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
0.500 inches first end
Precision Classification:
Quality number 10 or quality number 11
Material:
Steel comp 303
Material Specification:
Qq-s-764, type 303, cond a federal specification single material response

NSN 3020-00-580-4313 Spur Gear - Page 2 of 2

Fiig: A27300



Style Designator:
Protruding hub
Supplementary Features:
Passivate, nav/ord specification od 15444, type 16
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No