## NSN 3020-00-580-4334

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-580-4334

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
Between 0.3105 inches and 0.3115 inches
Teeth Quantity:
20
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc axially through body, first end
Mounting Hole Thready Qty Per Inch (tpi):
56 axially through body, first end
Mounting Hole Thread Size:
0.086 inches axially through body, first end
Mounting Hole Type And Quantity:
1 plain axially through body, first end and 1 threaded axially through body, first end
Outside Diameter:
0.340 inches
Nominallength:
0.320 inches
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.180 inches first end
Face Width:
0.140 inches
Bore Diameter:
0.155 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
0.250 inches first end
Mounting Hole Diameter:
0.031 inches transversely through hub, first end
Material:
Steel comp 303
Material Specification:
Mil-s-7720, comp 303s military specification single material response
Surface Treatment:

Passivate

## NSN 3020-00-580-4334

Spur Gear - Page 2 of 2



Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300

Mil-std (military Standard):

Mil-s-7720 spec.