NSN 3020-00-580-4389



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-580-4389 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.9531 inches **Teeth Quantity:** 61 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end **Mounting Hole Thread Size:** 0.112 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 plain transversely through hub, first end and 1 threaded transversely through hub, first end **Outside Diameter:** 0.984 inches Nominallength: 0.375 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.219 inches first end **Face Width:** 0.156 inches **Bore Diameter:** 0.187 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.375 inches first end **Precision Classification:**

Quality number 10 or quality number 11 **Mounting Hole Diameter:**

0.041 inches transversely through hub, first end

Material:

Steel comp 303

NSN 3020-00-580-4389

Spur Gear - Page 2 of 2



Material Specification:
Qq-s-764, type 303, cond a federal specification single material response
Style Designator:

Protruding hub

Supplementary Features:

Passivate, nav/ord, spec od15444, type 16

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300