## NSN 3020-00-583-0089

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-583-0089 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: Between 0.6542 inches and 0.6562 inches **Teeth Quantity:** 21 **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 32 transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 0.718 inches Nominallength: 0.438 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.250 inches first end **Face Width:** 0.188 inches **Bore Diameter:** 0.313 inches both ends **Precision Classification:** Quality number 8 Material: Steel comp 303 **Material Specification:** Qq-s-763, class303 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Style Designator:** Protruding hub

Shelf Life: N/a

## NSN 3020-00-583-0089

Spur Gear - Page 2 of 2



		. ~				
ı	ını	t Of	· M	മമ	CII	re.

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-f-14072 spec.