## NSN 3020-00-583-0214

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-583-0214

| Body Style:   |
|---|
| Webbed, offset, with lightening holes                                 |
| Pitch Diameter:   |
| 13.5000 inches  |
| Teeth Quantity:   |
| 216   |
| Bore Style:   |
| W/counterbore counterbore, first end                                  |
| Hardness Rating:  |
| 81.5 rockwell superficial 15-n and 94.0 rockwell superficial 15-n     |
| Outside Diameter:   |
| 13.593 inches   |
| Tooth Form:   |
| Standard  |
| Pressure Angle:   |
| 20.0000 degrees   |
| Distance Between Body Face And Protruding Hub End:                    |
| 1.250 inches first end  |
| Body Recess Depth:  |
| 0.750 inches second end   |
| Face Width:   |
| 1.250 inches  |
| Bore Diameter:  |
| 4.312 inches counterbore, first end                                   |
| Counterbore Depth:  |
| 1.188 inches counterbore, first end                                   |
| Counterbore Diameter:   |
| 5.995 inches counterbore, first end                                   |
| Hub Style Designator:   |
| Plain first end   |
| Hub Diameter:   |
| 6.745 inches first end  |
| Material:   |
| Steel   |
| Material Specification:   |
| Ams 6470 assn standard single material response                       |
| Surface Treatment:  |
| Oxide   |
| Surface Treatment Specification:                                      |
| Mil-c-13924, class 2 military specification single treatment response |
| Style Designator:   |
|   |

Protruding hub, recessed body

## NSN 3020-00-583-0214

Spur Gear - Page 2 of 2



| N/a               |
|-------------------|
| Unit Of Measure:  |
|                   |
| Demilitarization: |
| No                |
| Fiig:             |
| A27300            |

Shelf Life:

Mil-std (military Standard):

Mil-c-13924 spec.