NSN 3020-00-585-9911

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-585-9911

Outside Diameter:

Between 1.083 inches and 1.088 inches

Overall Length:

Between 0.510 inches and 0.515 inches

Bore Diameter:

Between 0.3750 inches and 0.3756 inches

Bore Length:

Between 0.510 inches and 0.515 inches

Drilled Hole Diameter:

0.093 inches

Pitch Diameter:

0.966 inches

Securing Hole Quantity:

1

Face Width:

Between 0.106 inches and 0.114 inches

Design Form:

Plain

Bore Type:

Straight

Counterbore Feature:

Not included

Hole Location:

Located 0.248 in. From end of hubon radial axis

Keying Facility:

Not included

Securing Method:

Drilled hole

Lightening Hole:

Not included

Protruding Hub Characteristic:

Plain

Securing Location:

Aa end

Belt/chain/film Size For Which Designed:

Roller chain

Roller Chain Pitch Type For Which Designed:

Single pitch

Teeth Row Quantity:

1

Teeth Quantity Per Row:

12

NSN 3020-00-585-9911

Sprocket Wheel - Page 2 of 2



Asa Standard Chain Number: 25 Hardness Rating Test Method: Not rated **Bore Bearing:** Not included Hub External Keyway: Not included **Tooth Pitch:** 0.250 inches Hub End Outside Diameter And Location: 0.625 inches both ends Distance From Outside Flange/rim To Hub End And Location: 0.404 inches both ends Material: Steel, sae 1040 Material: Steel comp 1040 **Material Specification:** Sae 1040 assn standard single material response **Surface Treatment:** Cadmium Style Designator: Plain Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig:

T353-c