NSN 3020-00-588-9529

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-588-9529

g
Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
0.9380 inches
Teeth Quantity:
45
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thread Size:
0.086 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end
Outside Diameter:
0.977 inches
Nominallength:
0.281 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.188 inches first end
Face Width:
0.093 inches
Bore Diameter:
0.188 inches both ends
Hub Style Designator:
Plain second end
Hub Diameter:
0.210 inches second end
End Length:
0.173 inches first end
End Diameter:
0.210 inches first end
First Step Length:
0.015 inches first end

First Step Diameter: 0.375 inches first end

NSN 3020-00-588-9529

Spur Gear - Page 2 of 2

Mil-a-8625 spec.



Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, t4 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Style Designator:
One protruding hub, one flush hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):