NSN 3020-00-600-8068

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-600-8068

Pitch Diameter:

Between 0.9990 inches and 1.0000 inches

Teeth Quantity:

120

Bore Style:

Plain both ends

Outside Diameter:

1.016 inches

Nominallength:

0.375 inches

Tooth Form:

Standard

Pressure Angle:

20.0000 degrees

Distance Between Body Face And Protruding Hub End:

0.250 inches first end

Face Width:

0.125 inches

Bore Diameter:

0.125 inches both ends

Hub Style Designator:

Pinned first end

Hub Diameter:

0.375 inches first end

Precision Classification:

Quality number 10

Material:

Steel comp 303 hub

Material Specification:

Qq-s-764, cond a federal specification single material response hub

Surface Treatment:

Passivate hub

Surface Treatment Specification:

Mil-f-14072, finish e300 military specification single treatment response hub

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 3020-00-600-8068

Spur Antibacklash Gear - Page 2 of 2

Fiig: A27300

Mil-std (military Standard):

Mil-a-8625 spec.

