NSN 3020-00-607-0083

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-607-0083

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
3.5000 inches
Teeth Quantity:
224
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Mounting Hole Thread Series Designator:
Unf transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
32 transversely through hub, first end
Mounting Hole Thread Size:
0.190 inches transversely through hub, first end
Mounting Hole Type And Quantity:
2 threaded transversely through hub, first end
Outside Diameter:
3.531 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.032 inches second end
Face Width:
0.125 inches
Bore Diameter:
1.750 inches both ends
Hub Style Designator:
Plain second end
Hub Diameter:
2.500 inches first end
Precision Classification:
Quality number 10 or quality number 11
First Groove Width:
0.421 inches first end
First Groove Diameter:
2.375 inches first end

NSN 3020-00-607-0083 Spur Gear - Page 2 of 2

Fiig: A27300



Distance From End To First Groove:
0.780 inches first end
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, t4 federal specification single material response
Surface Treatment:
Anodize
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No