NSN 3020-00-607-2326



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-607-2326 **Body Style:** Plain, solid **Spline Quantity:** 27 both ends **Attachment Method:** Mounting hole Pitch Diameter: 1.9512 inches **Teeth Quantity:** 20 **Bore Style:** Involute spline both ends **Spline Pitch Diameter:** 0.8440 inches both ends Hardness Rating: 33.0 rockwell c and 38.0 rockwell c **Mounting Hole Type And Quantity:** 5 plain transversely through hub, first end **Outside Diameter:** 2.100 inches Nominallength: 1.150 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.450 inches first end **Face Width:** 0.700 inches **Bore Diameter:** 0.865 inches both ends **Counterbore Depth:** 0.410 inches second end **Counterbore Diameter:** 1.560 inches second end **Hub Style Designator:** Pinned first end

Hub Diameter:

Quality number 8

1.270 inches first end

Precision Classification:

NSN 3020-00-607-2326

Spur Gear - Page 2 of 2



Mounting Hole Diameter:

0.312 inches transversely through hub, first end

Special Features:

Mtg holes spaced 72 degrees apart

Material:

Steel comp 4140

Material Specification:

Qq-s-624 federal specification single material response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300