NSN 3020-00-607-2383



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-607-2383 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 1.7500 inches **Teeth Quantity:** 84 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 32 transversely through hub, first end **Mounting Hole Thread Size:** 0.164 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 1.791 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.275 inches first end Distance Between Body Face And Recessed Hub End: 0.100 inches second end **Face Width:** 0.125 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** Plain second end **Hub Diameter:** 0.298 inches second end **End Length:** 0.140 inches first end **Precision Classification:**

Quality number 10 or quality number 11

End Diameter:

0.560 inches first end

NSN 3020-00-607-2383

Spur Gear - Page 2 of 2



| First Step Length: |
|--------------------------------------|
| 0.130 inches first end |
| First Step Diameter: |
| 1.200 inches first end |
| Material: |
| Copper alloy |
| Style Designator: |
| One protruding hub, one recessed hub |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A27300