NSN 3020-00-607-2565

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-607-2565 **Body Style:** Webbed, solid **Spline Quantity:** 21 both ends Pitch Diameter: 6.0000 inches **Teeth Quantity:** 36 **Bore Style:** Involute spline both ends **Backlash Designation:** Grade c **Hardness Rating:** 33.0 rockwell c and 38.0 rockwell c **Outside Diameter:** 6.250 inches Nominallength: 1.080 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.083 inches first end **Face Width:** 0.995 inches **Bore Diameter:** 1.420 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 1.312 inches first end **Precision Classification:** Quality number 6 or quality number 7

Material:

Steel

Material Specification:

Mil-s-11415 military specification single material response

Surface Treatment:

Phosphate manganese and phosphate zinc

Surface Treatment Specification:

Mil-p-16232, type m, class 1 military specification single treatment response and mil-p-16232, type z, class 1 military specification single treatment response

NSN 3020-00-607-2565

Spur Gear - Page 2 of 2



Style Designator:
One protruding hub, one flush hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300

Mil-std (military Standard):

Mil-s-11415 spec.