NSN 3020-00-607-2570



Bevel Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-607-2570 **Body Style:** Plain, solid **Spline Quantity:** 21 both ends Pitch Diameter: 3.0000 inches **Teeth Quantity:** 24 **Bore Style:** Involute spline both ends **Spline Pitch Diameter:** 1.3125 inches both ends **Backlash Designation:** Grade c Hardness Rating: 55.0 rockwell c and 60.0 rockwell c **Outside Diameter:** 3.1770 inches Nominallength: 1.518 inches Teeth Type: Straight Pressure Angle: 20.0000 degrees Pitch Angle: 45.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.750 inches second end **Body Recess Depth:** 0.1743 inches first end **Face Width:** 0.750 inches **Bore Diameter:** 1.425 inches both ends **Hub Style Designator:** Plain second end **Hub Diameter:** 1.875 inches second end **Precision Classification:**

Quality number 6 or quality number 7

Material: Steel

NSN 3020-00-607-2570

Bevel Gear - Page 2 of 2



_	•		_				
•	ırfa	2	l r	02	tm	Δn	

Phosphate manganese and phosphate zinc

Surface Treatment Specification:

Mil-p-16232, type m, class 1 military specification single treatment response and mil-p-16232, type z, class 1 military specification 1st treatment response

Style Designator:

Peripheral face, back hub protruding

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-p-16232 spec.