NSN 3020-00-609-3297

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-609-3297

Padu Stulai
Body Style:
Webbed, offset, solid
Attachment Method:
Mounting hole Pitch Diameter:
11.0000 inches
Teeth Quantity:
176
Bore Style: Plain both ends
Hardness Rating:
200.0 brinell standard and 250.0 brinell standard
Mounting Hole Type And Quantity:
6 countersunk axially through body, first end and 1 plain axially through body, first end
Outside Diameter:
11.124 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.125 inches first end
Body Recess Depth:
0.125 inches second end
Face Width:
0.500 inches
Bore Diameter:
6.250 inches both ends
Hub Style Designator:
Plain first end
Hub Diameter:
10.250 inches first end
Mounting Hole Diameter:
0.359 inches axially through body, first end
Bolt Hole Circle Diameter:
8.250 inches axially through body, first end
Material:
Steel comp 4140
Material Specification:
66 federal standard single material response and aisi/sae 4140 assn standard single material response
Surface Treatment:

Phosphate

NSN 3020-00-609-3297

Spur Gear - Page 2 of 2



Mil-p-16232, type 1, class 1 military specification single treatment response

Style Designator:

Protruding hub, recessed body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-p-16232 spec.