
NSN 3020-00-614-5596

Sprocket Wheel - Page 1 of 2





Outside Diameter:

15.740 inches

Bolt Circle Diameter:

12.000 inches

Bore Diameter:

Between 9.750 inches and 9.755 inches

Bore Length:

0.168 inches

Drilled Hole Diameter:

0.438 inches

Pitch Diameter:

15.318 inches

Securing Hole Quantity:

6

Face Width:

0.168 inches

Design Form:

Plain

Bore Type:

Straight

Counterbore Feature:

Not included

Hole Location:

Located through face equally spaced

Keying Facility:

Not included

Securing Method:

Drilled hole

Lightening Hole:

Not included

Securing Location:

Both ends

Belt/chain/film Size For Which Designed:

Roller chain

Roller Chain Pitch Type For Which Designed:

Single pitch

Teeth Row Quantity:

1

Teeth Quantity Per Row:

130

Asa Standard Chain Number:

35

NSN 3020-00-614-5596

Sprocket Wheel - Page 2 of 2



Hardness Rating Test Method: Not rated **Bore Bearing:** Not included Hub External Keyway: Not included **Tooth Pitch:** 0.375 inches Material: Steel, fed standard no. 66, aisi 1023 or sae 1023 Material: Steel, fed standard no. 66, aisi 1023 or sae 1023 Style Designator: Plain Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: T353-c