## NSN 3020-00-614-5854

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-614-5854

Body Style:
Plain, solid
Pitch Diameter:
Between 2.0302 inches and 2.0312 inches
Teeth Quantity:
130
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Outside Diameter:
2.061 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.250 inches first end
Face Width:
0.187 inches
Bore Diameter:
0.250 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
0.500 inches first end
Precision Classification:
Quality number 10
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, t4 federal specification single material response
Surface Treatment:
Anodize hub
Surface Treatment Specification:
Mil-a-8625, type 1 military specification single treatment response hub
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 3020-00-614-5854

Spur Gear - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.