## NSN 3020-00-618-6414

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-618-6414

**Body Style:** Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 1.1875 inches **Teeth Quantity:** 38 **Bore Style:** W/ keyway both ends **Mounting Hole Thread Series Designator:** Unf transversely through hub, first end **Mounting Hole Thread Size:** 0.190 inches transversely through hub, first end Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end **Outside Diameter:** 1.250 inches **Tooth Form:** Standard **Pressure Angle:** 14.5000 degrees **Distance Between Body Face And Protruding Hub End:** 0.500 inches first end Face Width: 0.438 inches **Bore Diameter:** 0.438 inches both ends **Keyway Width:** 0.094 inches both ends **Distance From Bore Center To Keyway Bottom:** 0.266 inches both ends Hub Style Designator: Plain first end **Hub Diameter:** 0.875 inches first end Material: Steel comp 303 **Material Specification:** Qq-s-764, cond a federal specification single material response Surface Treatment:

Passivate

# NSN 3020-00-618-6414

Spur Gear - Page 2 of 2



#### Surface Treatment Specification:

Mil-f-14072, finish e300 military specification single treatment response

#### Style Designator:

Protruding hub

Shelf Life:

N/a

### Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-f-14072 spec.