# NSN 3020-00-626-9188

Bevel Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-626-9188

**Body Style:** Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 2.1666 inches **Teeth Quantity:** 26 **Bore Style:** W/ keyway both ends Mounting Hole Thread Series Designator: Unf transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 32 transversely through hub, first end Hardness Rating: 48.0 rockwell c teeth and 52.0 rockwell c teeth Mounting Hole Thread Size: 0.190 inches transversely through hub, first end Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end **Outside Diameter:** 2.221 inches Nominallength: 1.232 inches **Teeth Type:** Straight **Pressure Angle:** 20.0000 degrees **Pitch Angle:** 60.0167 degrees **Distance Between Body Face And Protruding Hub End:** 0.719 inches second end **Body Recess Depth:** 0.1070 inches first end Face Width: 0.406 inches **Bore Diameter:** 0.750 inches both ends Bore Depth: 1.125 inches both ends **Keyway Width:** 

0.124 inches both ends

# NSN 3020-00-626-9188

Bevel Gear - Page 2 of 2



## Distance From Bore Center To Keyway Bottom:

0.443 inches both ends

#### Hub Style Designator:

Pinned second end

#### Hub Diameter:

1.250 inches second end

## **Special Features:**

Distance from second end of hub to center of tapped hole 0.375 nom. In.

#### Material:

Steel

## Surface Treatment:

Oxide

# Surface Treatment Specification:

Mil-c-13924, class 2 military specification single treatment response

#### Style Designator:

Peripheral face, back hub protruding

## Shelf Life:

N/a

#### Unit Of Measure:

Demilitarization:

No

---

Fiig:

A27300

#### Mil-std (military Standard):

Mil-c-13924 spec.