NSN 3020-00-628-0238

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-628-0238 **Pitch Diameter:** 1.1718 inches **Teeth Quantity:** 75 **Bore Style:** Plain both ends **Backlash Designation:** Grade d **Outside Diameter:** 1.2031 inches Nominallength: 0.375 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.250 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.375 inches first end **Precision Classification:** Quality number 12 Material: Steel comp 302 or steel comp 303 or steel comp 416 **Material Specification:** Fed standard 66, aisi 302/sae30302 federal standard 1st material response or federal standard 66, aisi 303.Sae 30303 federal standard 2nd material response or federal standard 66, aisi 416.Sae 51416 federal standard 3rd material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil f 14072 military specification single treatment response **Style Designator:** Protruding hub

N/a

Shelf Life:

Unit Of Measure:

NSN 3020-00-628-0238

Spur Antibacklash Gear - Page 2 of 2



em			

No

Fiig:

A27300

Mil-std (military Standard):

spec.