## NSN 3020-00-630-0553

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-630-0553

Outside Diameter:
Between 0.623 inches and 0.627 inches
Overall Length:
0.631 inches
Thread Size:
0.138-32
Bore Diameter:
Between 0.187 inches and 0.188 inches
Bore Length:
0.631 inches
Pitch Diameter:
0.561 inches
Securing Hole Quantity:
2
Face Width:
0.048 inches
Design Form:
Plain
Bore Type:
Straight
Counterbore Feature:
Not included
Hole Location:
Thru bore
Keying Facility:
Not included
Securing Method:
Threaded hole
Lightening Hole:
Not included
Protruding Hub Characteristic:
Plain
Belt/chain/film Size For Which Designed:
16 millimeter film
Teeth Row Quantity:
2
Center To Center Distance Between Teeth Rows:
0.484 inches
Teeth Quantity Per Row:
6
Hardness Rating Test Method:

Not rated

## **NSN 3020-00-630-0553** Sprocket Wheel - Page 2 of 2



Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.295 inches
Hub End Outside Diameter And Location:
0.564 inches both ends
Distance From Outside Flange/rim To Hub End And Location:
0.049 inches both ends
Material:
Steel, qq-s-763, class 303, cond b
Material:
Steel comp 303
Material Specification:
Qq-s-763, class 303, cond b federal specification single material response
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c