NSN 3020-00-630-6379

Spur Gear - Page 1 of 2

Body Style: Plain, solid



View Online at https://aerobasegroup.com/nsn/3020-00-630-6379

| Attachment Method: |
|--|
| Mounting hole |
| Pitch Diameter: |
| 2.3750 inches |
| Teeth Quantity: |
| 114 |
| Bore Style: |
| W/counterbore counter bore, second end |
| Mounting Hole Type And Quantity: |
| 3 counterbored axially through hub, first end |
| Outside Diameter: |
| 2.415 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.782 inches first end |
| Face Width: |
| 0.156 inches |
| Bore Diameter: |
| 0.750 inches counter bore, second end |
| Counterbore Depth: |
| 0.812 inches counter bore, second end |
| Counterbore Diameter: |
| 1.312 inches counter bore, second end |
| Hub Style Designator: |
| 1 step first end |
| End Length: |
| 0.654 inches first end |
| End Diameter: |
| 2.057 inches first end |
| First Step Length: |
| 0.127 inches first end |
| First Step Diameter: |
| 2.187 inches first end |
| Mounting Hole Diameter: |
| 0.200 inches axially through hub, first end |
| Material: |
| Aluminum alloy 6061 |

NSN 3020-00-630-6379

Spur Gear - Page 2 of 2

Fiig: A27300



| Material Specification: |
|---|
| Qq-a-225/8, t6 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Style Designator: |
| Protruding hub |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |