## NSN 3020-00-640-2772



Groove Pulley - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-640-2772 **Spline Major Diameter:** Between 0.874 inches and 0.875 inches **Groove Depth:** 0.688 inches **Groove Width:** Between 0.654 inches and 0.656 inches **Outside Diameter:** Between 7.082 inches and 7.098 inches **Overall Length:** 2.000 inches **Spline Quantity: Spline Minor Diameter:** Between 0.699 inches and 0.700 inches V Groove Angle In Deg: 36.0 **Pitch Diameter:** 6.590 inches **Material And Location:** Iron Face Width: 1.000 inches **Design Form:** Webbed **Bore Type:** Involute spline or spline or dam Spline Length: 2.000 inches **Groove Quantity: Counterbore Feature:** Not included **Keying Facility:** Not included **Split Hub Feature:** Not included Web/spoke Relationship To Face Centerline: Not offset **Lightening Hole:** 

Included
Integral Cooling Vane:
Not included

## **NSN 3020-00-640-2772**Groove Pulley - Page 2 of 2



Groove Shape:
V
Bore Feature:
Not included
Hub End Outside Diameter And Location:
1.281 inches aa end and 1.336 inches bb end and 1.340 inches bb end
Distance From Outside Flange/rim To Hub End And Location:
0.535 inches aa end and 0.541 inches aa end and 0.459 inches bb end and 0.465 inches bb end
Special Features:
4 ribs located on bb end spaced 90 degrees apart, 1/4 in. W and flush with face, 4 holes, 11/64 in. Dia, no. 12-24 nc thd located on 2.245 in
Min to 2.250 in. Maximum diameter bolt circle on rib s for securing fan
Style Designator:
Webbed or spoked
Fsc Application Data:
Engine generator drive
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
T353-a