## NSN 3020-00-640-4470

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-640-4470

Body Style:
Webbed, offset, solid
Attachment Method:
Mounting hole
Pitch Diameter:
3.5000 inches
Teeth Quantity:
49
Bore Style:
W/ keyway both ends
Backlash Designation:
Grade a
Hardness Rating:
60.0 rockwell c teeth
Mounting Hole Type And Quantity:
4 plain axially through body, first end
Outside Diameter:
3.613 inches
Nominallength:
0.443 inches
Tooth Form:
Standard
Pressure Angle:
00.0000
20.0000 degrees
20.0000 degrees  Distance Between Body Face And Protruding Hub End:
Distance Between Body Face And Protruding Hub End:
Distance Between Body Face And Protruding Hub End: 0.010 inches first end
Distance Between Body Face And Protruding Hub End: 0.010 inches first end Body Recess Depth:
Distance Between Body Face And Protruding Hub End: 0.010 inches first end Body Recess Depth: 0.165 inches second end
Distance Between Body Face And Protruding Hub End: 0.010 inches first end Body Recess Depth: 0.165 inches second end Face Width:
Distance Between Body Face And Protruding Hub End: 0.010 inches first end Body Recess Depth: 0.165 inches second end Face Width: 0.438 inches
Distance Between Body Face And Protruding Hub End: 0.010 inches first end Body Recess Depth: 0.165 inches second end Face Width: 0.438 inches Bore Diameter:
Distance Between Body Face And Protruding Hub End:  0.010 inches first end  Body Recess Depth:  0.165 inches second end  Face Width:  0.438 inches  Bore Diameter:  0.990 inches both ends
Distance Between Body Face And Protruding Hub End:  0.010 inches first end  Body Recess Depth:  0.165 inches second end  Face Width:  0.438 inches  Bore Diameter:  0.990 inches both ends  Keyway Width:
Distance Between Body Face And Protruding Hub End:  0.010 inches first end  Body Recess Depth:  0.165 inches second end  Face Width:  0.438 inches  Bore Diameter:  0.990 inches both ends  Keyway Width:  0.194 inches both ends
Distance Between Body Face And Protruding Hub End:  0.010 inches first end  Body Recess Depth:  0.165 inches second end  Face Width:  0.438 inches  Bore Diameter:  0.990 inches both ends  Keyway Width:  0.194 inches both ends  Distance From Bore Center To Keyway Bottom:
Distance Between Body Face And Protruding Hub End:  0.010 inches first end  Body Recess Depth:  0.165 inches second end  Face Width:  0.438 inches  Bore Diameter:  0.990 inches both ends  Keyway Width:  0.194 inches both ends  Distance From Bore Center To Keyway Bottom:  0.094 inches both ends
Distance Between Body Face And Protruding Hub End:  0.010 inches first end  Body Recess Depth:  0.165 inches second end  Face Width:  0.438 inches  Bore Diameter:  0.990 inches both ends  Keyway Width:  0.194 inches both ends  Distance From Bore Center To Keyway Bottom:  0.094 inches both ends  Hub Style Designator:
Distance Between Body Face And Protruding Hub End:  0.010 inches first end  Body Recess Depth:  0.165 inches second end  Face Width:  0.438 inches  Bore Diameter:  0.990 inches both ends  Keyway Width:  0.194 inches both ends  Distance From Bore Center To Keyway Bottom:  0.094 inches both ends  Hub Style Designator:  Plain first end
Distance Between Body Face And Protruding Hub End:  0.010 inches first end  Body Recess Depth:  0.165 inches second end  Face Width:  0.438 inches  Bore Diameter:  0.990 inches both ends  Keyway Width:  0.194 inches both ends  Distance From Bore Center To Keyway Bottom:  0.094 inches both ends  Hub Style Designator:  Plain first end  Hub Diameter:

## NSN 3020-00-640-4470

Spur Gear - Page 2 of 2



## **Bolt Hole Circle Diameter:**

2.240 inches axially through body, first end

Material:

Steel comp e9310

**Material Specification:** 

Ams 6260 assn standard single material response

Style Designator:

Protruding hub, recessed body

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300