NSN 3020-00-651-8667

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-651-8667

Counterbore Diameter:
2.000 inches
Counterbore Depth:
0.188 inches
Outside Diameter:
Between 3.915 inches and 3.920 inches
Overall Length:
2.438 inches
Bore Diameter:
Between 1.5000 inches and 1.5020 inches
Bore Length:
2.438 inches
Pitch Diameter:
3.599 inches
Face Width:
0.343 inches
Design Form:
Plain
Bore Type:
Straight
Counterbore Feature:
Included
Counterbore Location:
Bb end
Keying Facility:
Not included
Lightening Hole:
Not included
Protruding Hub Characteristic:
Plain or stepped
Groove/step Location:
Aa end
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
1
Teeth Quantity Per Row:
18
Asa Standard Chain Number:

50

NSN 3020-00-651-8667 Sprocket Wheel - Page 2 of 2



Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.625 inches
Hub End Outside Diameter And Location:
2.375 inches bb end
Distance From Outside Flange/rim To Hub End And Location:
1.016 inches bb end
First Step Face Largest Diameter And Location:
2.375 inches aa end
First Step Length And Location:
0.500 inches aa end
Second Step Length And Location:
0.5785 inches aa end
Hub End Outside Diameter And Location:
1.995 inches aa end and 2.000 inches aa end
Special Features:
Second hub end tapered, 0.376 in. Lg of taper, 2.250 in. Dia. Oftaper at small end
Material:
Steel, qq-s-681, class 120-95
Material:
Steel comp 120-95
Material Specification:
Qq-s-681, class 120-95 federal specification single material response
Surface Treatment:
Phosphate
Style Designator:
Plain
Surface Treatment:
Phosphate
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filig:
T353-c