NSN 3020-00-652-1171

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-652-1171

| g |
|--|
| Body Style: |
| Webbed, solid |
| Attachment Method: |
| Mounting hole |
| Pitch Diameter: |
| 1.8250 inches |
| Teeth Quantity: |
| 73 |
| Bore Style: |
| Plain both ends |
| Hardness Rating: |
| 30.0 rockwell c and 46.0 rockwell c |
| Mounting Hole Type And Quantity: |
| 3 plain transversely through hub, first end |
| Outside Diameter: |
| 1.850 inches |
| Nominallength: |
| 0.530 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 25.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.520 inches second end |
| Body Recess Depth: |
| 0.520 inches first end |
| Face Width: |
| 0.100 inches |
| Bore Diameter: |
| 0.615 inches both ends |
| Hub Style Designator: |
| Plain second end |
| Hub Diameter: |
| 1.000 inches second end |

Mounting Hole Diameter:

0.100 inches transversely through hub, first end

Bolt Hole Circle Diameter:

0.750 inches transversely through hub, first end

Special Features:

Mounting holes on flange extends through bell

Material:

Steel comp 416se

NSN 3020-00-652-1171

Spur Gear - Page 2 of 2



| Material Specification |
|------------------------|
|------------------------|

Ams 5610 assn standard single material response

Style Designator:

Bell shape body, protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300