NSN 3020-00-657-5972

Bevel Gear - Page 1 of 2

Body Style:

Webbed, offset, solid



View Online at https://aerobasegroup.com/nsn/3020-00-657-5972

Attachment Method:
Mounting hole
Pitch Diameter:
4.0000 inches
Teeth Quantity:
20
Bore Style:
Plain both ends
Hardness Rating:
26.0 rockwell c teeth and 40.0 rockwell c teeth
Mounting Hole Type And Quantity:
3 plain axially through body, first end
Outside Diameter:
4.283 inches
Nominallength:
3.625 inches
Teeth Type:
Straight
Pressure Angle:
20.0000 degrees
Pitch Angle:
45.0000 degrees
Distance Between Body Face And Protruding Hub End:
2.750 inches second end
Face Width:
0.850 inches
Bore Diameter:
1.250 inches both ends
Hub Style Designator:
Externally splined, involute splines second end
Mounting Hole Diameter:
0.188 inches axially through body, first end
Bolt Hole Circle Diameter:
2.000 inches axially through body, first end
Hub Spline Quantity:
33 second end
Hub Spline Pitch Diameter:
1.6500 inches second end
Material:

Steel comp 8620 or steel comp 4620h

NSN 3020-00-657-5972

Bevel Gear - Page 2 of 2

No Fiig: A27300

Mil-std (military Standard):

Mil-c-14550 spec.



Material Specification:
Qq-s-624, cond n federal specification all material responses
Surface Treatment:
Copper teeth
Surface Treatment Specification:
$\label{eq:mil-c-14550} \mbox{Mil-c-14550, class 3 or 4 military specification single treatment response teeth}$
Style Designator:
Peripheral face, back hub protruding
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: