NSN 3020-00-670-6472

0.089 inches transversely through hub, first end

Helical Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-670-6472

| Body Style: |
|--|
| Plain, solid |
| Attachment Method: |
| Mounting hole |
| Pitch Diameter: |
| 0.5424 inches |
| Teeth Quantity: |
| 17 |
| Bore Style: |
| Plain both ends |
| Mounting Hole Thread Series Designator: |
| Unc transversely through hub, first end |
| Hardness Rating: |
| 48.0 rockwell c teeth and 52.0 rockwell c teeth |
| Mounting Hole Thread Size: |
| 0.112 inches transversely through hub, first end |
| Mounting Hole Type And Quantity: |
| 1 plain transversely through hub, first end and 2 threaded transversely through hub, first end |
| Outside Diameter: |
| 0.6040 inches |
| Teeth Type: |
| Single helix |
| Tooth Form: |
| Standard |
| Tooth Direction: |
| Left |
| Pressure Angle: |
| 20.0000 degrees |
| Helix Angle: |
| 11.6332 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.462 inches first end |
| Face Width: |
| 0.250 inches |
| Bore Diameter: |
| 0.2503 inches both ends |
| Hub Style Designator: |
| Plain both ends |
| Hub Diameter: |
| 0.420 inches both ends |
| Mounting Hole Diameter: |

NSN 3020-00-670-6472

Helical Gear - Page 2 of 2

Mil-std (military Standard):

Mil-s-5626 spec.



| Material: |
|--|
| Steel comp 4140 |
| Material Specification: |
| Mil-s-5626, cond f military specification single material response |
| Surface Treatment: |
| Oxide |
| Style Designator: |
| Protruding hubs |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A27300 |