NSN 3020-00-671-1183

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-671-1183

Body Style:
Webbed, offset, solid
Attachment Method:
Mounting hole
Pitch Diameter:
1.1250 inches
Teeth Quantity:
90
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
56 transversely through hub, first end
Mounting Hole Thread Size:
0.086 inches transversely through hub, first end
Mounting Hole Type And Quantity:
2 threaded transversely through hub, first end
Outside Diameter:
1.150 inches
Nominallength:
0.359 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.269 inches first end
Body Recess Depth:
0.044 inches second end
Face Width:
0.090 inches
Bore Diameter:
0.187 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
0.437 inches first end
Precision Classification:
Quality number 9
Material:
material.

Aluminum alloy 2024

NSN 3020-00-671-1183

Spur Gear - Page 2 of 2



Material Specification: Qq-a-225/6, t4 federal specification single material response Surface Treatment: Chromate Surface Treatment Specification: Mil-c-5541 military specification single treatment response Style Designator: Protruding hub, recessed body Shelf Life: N/a Unit Of Measure: - Demilitarization: No

Mil-std (military Standard): Mil-c-5541 spec.

Fiig: A27300