## NSN 3020-00-671-1184

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-671-1184 **Body Style:** Webbed, offset, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.9375 inches **Teeth Quantity:** 75 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 0.962 inches Nominallength: 0.226 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.133 inches first end **Face Width:** 0.093 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** Plain second end **Hub Diameter:** 0.562 inches first end **Precision Classification:** Quality number 9 Material: Aluminum alloy 2024

**Material Specification:** 

Qq-a-250/4, t3 federal specification single material response

## NSN 3020-00-671-1184

Spur Gear - Page 2 of 2

Mil-std (military Standard):

Mil-c-5541 spec.



Surface Treatment:
Chromate
Surface Treatment Specification:
Mil-c-5541 military specification single treatment response
Style Designator:
One protruding hub, one flush hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300