NSN 3020-00-671-4550

Helical Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-671-4550

| Body Style: |
|--|
| Plain, solid |
| Pitch Diameter: |
| 3.4910 inches |
| Teeth Quantity: |
| 35 |
| Bore Style: |
| Tapered w/keyway first end |
| Hardness Rating: |
| 335.0 brinell standard and 375.0 brinell standard |
| Outside Diameter: |
| 3.663 inches |
| Teeth Type: |
| Single helix |
| Tooth Form: |
| Standard |
| Tooth Direction: |
| Right |
| Pressure Angle: |
| 30.7995 degrees |
| Helix Angle: |
| 30.0483 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.281 inches first end |
| Face Width: |
| 1.250 inches |
| Keyway Width: |
| 0.314 inches first end |
| Distance From Bore Center To Keyway Bottom: |
| 0.873 inches first end |
| Taper Major Diameter: |
| 1.370 inches first end |
| Hub Style Designator: |
| Plain first end |
| Hub Diameter: |
| 2.250 inches first end |
| Special Features: |
| 2nd end counterbored, 2.188 in. Diameter by 0.375 in. Dp |
| Material: |
| Steel |
| Material Specification: |
| Mil-s-890, alloy no. 1 military specification single material response |
| |

NSN 3020-00-671-4550

Helical Gear - Page 2 of 2



| Style Designator: |
|-------------------|
| Protruding hub |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| |
| No |
| No Fiig: |

Mil-std (military Standard):

Mil-s-890 spec.