## NSN 3020-00-673-1245

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-673-1245

**Body Style:** Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 0.9625 inches **Teeth Quantity:** 77 **Bore Style:** Plain both ends **Features Provided:** Casehardened Mounting Hole Thread Series Designator: Unc transversely through hub, first end Mounting Hole Thread Size: 0.086 inches transversely through hub, first end Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end **Outside Diameter:** 0.988 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.244 inches first end Face Width: 0.062 inches **Bore Diameter:** 0.120 inches both ends Hub Style Designator: 1 step first end End Length: 0.119 inches first end End Diameter: 0.218 inches first end First Step Length: 0.125 inches first end **First Step Diameter:** 0.625 inches first end **Special Features:** 

Grooved hub, 0.037 in. From end, 0.017 in. Wide

# NSN 3020-00-673-1245

Spur Gear - Page 2 of 2



Material:

Aluminum alloy 6061

## Material Specification:

Qq-a-225/8, t6 federal specification single material response

## Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

### Demilitarization:

No

#### Fiig:

A27300