NSN 3020-00-673-1249



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-673-1249 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 3.3750 inches **Teeth Quantity:** 270 **Bore Style:** W/counterbore both ends **Mounting Hole Thread Series Designator:** Unf axially through hub, first end **Mounting Hole Thread Size:** 0.060 inches axially through hub, first end **Mounting Hole Type And Quantity:** 4 threaded axially through hub, first end **Outside Diameter:** 3.400 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.532 inches first end **Face Width:** 0.127 inches **Bore Diameter:** 2.250 inches both ends **Counterbore Depth:** 0.766 inches first end **Counterbore Diameter:** 2.443 inches first end **Hub Style Designator:** Plain second end **Hub Diameter:** 2.687 inches first end First Groove Width: 0.282 inches first end First Groove Diameter: 2.672 inches first end

Distance From End To First Groove:

0.125 inches first end

NSN 3020-00-673-1249

Spur Gear - Page 2 of 2

Fiig: A27300



Material:
Aluminum alloy 6061
Material Specification:
Qq-a-250/11, t6 federal specification single material response
Surface Treatment:
Anodize
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli