## NSN 3020-00-673-6773



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-673-6773 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 3.3750 inches **Teeth Quantity:** 270 **Bore Style:** W/counterbore both ends **Mounting Hole Thread Series Designator:** Unf axially through hub, first end **Mounting Hole Thread Size:** 0.060 inches axially through hub, first end **Mounting Hole Type And Quantity:** 4 threaded axially through hub, first end **Outside Diameter:** 3.400 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.032 inches second end **Face Width:** 0.118 inches **Bore Diameter:** 2.690 inches both ends **Counterbore Depth:** 0.034 inches second end **Counterbore Diameter:** 2.813 inches second end **Hub Style Designator:** Plain second end **Hub Diameter:** 2.938 inches second end **End Length:** 0.095 inches first end **End Diameter:** 

First Step Length: 0.282 inches first end

2.750 inches first end

## NSN 3020-00-673-6773

Spur Gear - Page 2 of 2

**Fiig:** A27300



First Step Diameter:
2.968 inches first end
Special Features:
Mtg holes 90 degs apart
Material:
Aluminum alloy 6061
Material Specification:
Qq-a-250/11, t6 federal specification single material response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli