NSN 3020-00-673-6773

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-673-6773

Body Style: Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 3.3750 inches **Teeth Quantity:** 270 **Bore Style:** W/counterbore both ends Mounting Hole Thread Series Designator: Unf axially through hub, first end **Mounting Hole Thread Size:** 0.060 inches axially through hub, first end Mounting Hole Type And Quantity: 4 threaded axially through hub, first end **Outside Diameter:** 3.400 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.032 inches second end Face Width: 0.118 inches **Bore Diameter:** 2.690 inches both ends **Counterbore Depth:** 0.034 inches second end **Counterbore Diameter:** 2.813 inches second end Hub Style Designator: Plain second end **Hub Diameter:** 2.938 inches second end End Length: 0.095 inches first end End Diameter: 2.750 inches first end First Step Length:

0.282 inches first end

NSN 3020-00-673-6773

Spur Gear - Page 2 of 2



First Step Diameter:

2.968 inches first end

Special Features:

Mtg holes 90 degs apart

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, t6 federal specification single material response

Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A27300