NSN 3020-00-678-4238

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-678-4238

Body Style:

Webbed, offset, solid

Attachment Method:

Mounting hole

Pitch Diameter:

5.5000 inches

Teeth Quantity:

33

Bore Style:

Tapered w/keyway both ends

Mounting Hole Thread Series Designator:

Unf axially through body, first end

Mounting Hole Thready Qty Per Inch (tpi):

24 axially through body, first end

Hardness Rating:

45.0 rockwell c and 52.0 rockwell c

Mounting Hole Thread Size:

0.312 inches transversely through face

Mounting Hole Type And Quantity:

3 threaded axially through body, first end

Outside Diameter:

5.747 inches

Nominallength:

1.910 inches

Tooth Form:

Standard

Pressure Angle:

20.0000 degrees

Distance Between Body Face And Protruding Hub End:

1.030 inches first end

Distance Between Body Face And Recessed Hub End:

0.630 inches second end

Face Width:

0.880 inches

Keyway Width:

0.252 inches both ends

Distance From Bore Center To Keyway Bottom:

0.679 inches second end

Taper Major Diameter:

1.358 inches second end

Hub Style Designator:

Plain both ends

NSN 3020-00-678-4238

Spur Gear - Page 2 of 2



Hub Diameter:

2.090 inches second end

Bolt Hole Circle Diameter:

3.120 inches axially through body, first end

Material:

Steel

Material Specification:

Mil-s-13048 military specification single material response

Style Designator:

One protruding hub, one recessed hub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A27300

Mil-std (military Standard):

Mil-s-13048 spec.